

LP-CHOSF21001**10/100M SFP one port media converter chassis with external power supply**

LPCHOSF21001_SS_ENB01W

Features

- Complies with IEEE 802.3 10 Base-T standard.
- Complies with IEEE 802.3u 10/100 Base-TX/FX standard.
- Complies with IEEE 802.3X standard.
- 10/100Mbps port with full/half duplex auto negotiation.
- Back pressure flow control for full duplex.
- Converter mode with auto change forward (switch) function.
- Back pressure flow control for full/half duplex IEEE802.3X.
- Automatic identification of MDI/MDI-X cross line.



LP-CHOSF21001

10/100M SFP one port media converter chassis with external power supply

The **LP-CHOSF21001** 10/100M SFP one port media converter chassis, IEEE802.3u 100Mbps Fast Ethernet SFP Converter supports two types media for network connection such as 10/100Base-TX and 100Base-FX. The media converter is designed with a switch controller and buffer memory that connects two types segments to operate smoothly. With external power unit, it provides good stability and reliability.

Technical Specifications

Compliant Standards	IEEE802.3/u/z/ab, 10 Base-T, 100 Base-TX.
Interface Standards	Electrical Interface: RJ45, 10/100 Mbps. Optical Interface: SFP Port.
Optical Cable	UTP: Max Distance 100m. Fiber (Multimode): 50/125μm, 62.5/125 μm. Fiber (Singlemode): 8/125μm, 8.7/125μm, 9/125μm, 10/125 μm.
Flow Control	Full Duplex IEEE 802.3X Flow Control. Half Duplex backpressure Flow Control.
Environmental requirements	Environment temperature: -25°C~+50°C. Storage temperature: -35°C~+75°C. Rated Supply Voltage: AC85-260V/50Hz. MTBF: 100000 Hours. Power Loss: <5w (Input:DC5V 1000-3000mA).
Dimensions	11cm x 7cm x 2.5 cm (L) x (W) x (H)

How to Order

LP-CHOSF21001 10/100M SFP one port media converter chassis with external power supply

LanPro is continuously improving its products and reserves the right to change specifications and availability without prior notice.