

**LP-ICF31A1D401 Single Fiber Media Converter with BiDi technology,  
WDM, 10/100/1000M, 1550nm/1310nm, Singlemode for distances up to 40km, SC connector.**

LPICF31A1D401\_SS\_ENB01W

### Features

- Comply with 802.3z, 802.3ab Standard.
- Type BiDi One (1) Singlemode fiber for up to 40km.
- WDM Technology.
- TP port supports Auto-negotiation for automatic speed selection.
- TP port supports automatic MDI/MDIX crossover.
- Transmission distance: Singlemode 40km.
- Wave lengths: 1550nm/1310nm.
- LED indicators: PWR, TX-LNK, TX-ACT, FX-LNK, FX-ACT, FDX.
- Connector: one UTP RJ-45 connector and one SC connector.
- Power: External power supply: 5 VDC.
- Operating temperature: 0°C ~ 50°C.
- Storage temperature: -40 ~ 70°C.
- Humidity: 5-90% (non-condensing).



**LP-ICF31A1D401  
Single Fiber Media Converter with BiDi technology,  
WDM, 10/100/1000M, 1550nm/1310nm,  
Singlemode for distances up to 40km, SC  
connector.**

The LanPro's LP-ICF31A1D401 BiDi WDM 10/100/1000M Single Fiber Singlemode Media Converter exploit the WDM technology and it's Bi-Directional communication capability in order to support up to 40 km distances via a single optical fiber.

### A How to order:

**LP-ICF31A1D401**

Single Fiber Media Converter with BiDi technology,  
WDM, 10/100/1000M, 1550nm/1310nm, Singlemode  
for distances up to 40km, SC connector.

