

LP-07550 Modular Raceway**Section: 19.05 x 11.11 mm ($\frac{3}{4}$ x $\frac{7}{16}$ inches) length: 2 m (6.5 ft).**

LP07550_SS_ENB01W

Features

- Low cost solution for assembling the main raceway path of surface-mounted structured cabling.
- Compatible with the same section fittings for any type of installation.
- Facilitates installation of Category 5e, 6, 6A, 7, and fiber optic distribution.
- Section: 19.05 mm x 11.11 mm ($\frac{3}{4}$ x $\frac{7}{16}$ inches) x 2 m (6.5 ft) length.
- Material UL94V-0.

**LP-07550
Modular Raceway
Section: 19.05 x 11.11 mm ($\frac{3}{4}$ x $\frac{7}{16}$ inches)
length: 2 m (6.5 ft).**

The **LP-07550** is a modular raceway extruded with a section of 19.05 mm x 11.11 mm ($\frac{3}{4}$ x $\frac{7}{16}$ inches) and a length of 2 m (6.5 ft).

It is a very elegant and functional solution to build the main path in structured cabling protection of commercial, industrial, or residential environments affixed to a wall or surface.

Easy to cut to the required size.

It is a component of our line of products for cable management and comes with very strong and durable adhesive backing for fixing to a clean surface. The raceway is compatible with fittings of its size, surface boxes used for faceplates, ground cable guards, for cable management, etc.

Can be painted with a latex based paint, easy to install and use.

The raceway is manufactured with fire resistant PVC, compliant with UL94V-0.

It holds, guides, and protects wires carrying up to 600 Volt.

It is possible to supply it in custom colors by special order.

A Specifications

Model	LP-07550
Material	PVC
UL classification	UL94V-0
Color	White
Parts	2
Adhesion	Double face 3M tape
Uses	Voice, data, coax, audio, video, optical fiber (up to 600 VAC)
Dimensions	Width: 19.05 mm ($\frac{3}{4}$ " Height: 11.11 mm ($\frac{7}{16}$ " Length: 2 m (6.5')

B How to Order

LP-07550 Modular Raceway, section of 19.05 x 11.11 mm, ($\frac{3}{4}$ x $\frac{7}{16}$ inches), length of 2 m (6.5 ft).