

**LP-NTWE28004P5BK**

**Nylon Tie Wrap Extra Strength Grade,  
280mm x 4.5 mm, bundle diameter Min.3.2mm. Max.72mm, black color. Non releasable.**

LPNTWE28004P5BK\_SS\_ENB01W

**Features**

- Indoor/Outdoor capable.
- Bundle Diameter Min. 3.2mm  
Max. 72mm.
- Max. strength 49lb/f (220N).
- Dupont Nylon (no plastic).  
Meets UL 94V-2 flammability  
standards.
- Non releasable.
- 110lb (50kg) Death weight  
capable.
- UL Approved under E486356.  
US Regulations tested.
- Operating temperature: -40°C  
to +85°C (-40°F +185°F)



**LP-NTWE28004P5BK**  
**Nylon Tie Wrap Extra Strength Grade,**  
**280mm x 4.5mm, bundle diameter Min. 3.2mm**  
**Max.72mm, black color. Non releasable.**

Organize your cable bundles with colored LanPro non-releasable with extra strength nylon grade tie-wraps.

Made of durable and strong yet flexible Nylon 6-6 compound these non releasable cable ties are superb for the management of wire and cable bundles behind home theater, or any type of Computer equipment setup that are interconnected in a permanent installation.

Flame resistant as per UL 94V-2 standard come in several colors to suit your identification needs.

**A Specifications**

Model	Value
LP-NTWE28004P5BK	
Color	Black
Type	E=Tie Wraps Extra Strength Grade, Non Releasable
Material	N: Nylon 6-6
Length [mm]	280
Width [mm]	4.5
Bundle Diameter [mm]	Min 3.2/ Max 72
Flame resistance Standard	UL 94V-2
Minimum temperature [°C]	-40
Maximum temperature [°C]	+85

**B How to Order**

LP-NTWE28004P5BK Nylon Tie Wrap Extra Strength Grade, 280mm x 4.5mm, bundle diameter Min. 3.2mm. Max. 72mm, black color. Non releasable.

LanPro is continuously improving its products and reserves the right to change specifications and availability without prior notice.