LP-RU07101PDU Horizontal Rack-Mounted Protected Power Distribution Unit with Six (6) NEMA 5-15R Outlets with Thermomagnetic Overcurrent Protection.

LPRU07101PDU\_SS\_ENB01W



## Applications


The LP-RU07101PDU is an excellent choice for applications needing a feeder in the back or front of large cabinets and racks.

# LP-RU07101PDU

Horizontal Rack-Mounted Protected Power Distribution Unit with Six (6) NEMA 5-15R Outlets with Thermomagnetic Overcurrent Protection.

The **LP-RU07101PDU** is a horizontal rack mount style power strip, carrying six (6) NEMA 5-15R outlets for NEMA 5-15P equipment plugs, uses 1 U vertical space, and is constructed with a heavy duty steel enclosure and an on-off illuminated switch with finger guard cover that avoids accidental shut-down of the load.

#### **PDU Horizontal Installation**



#### A

#### Thermomagnetic Breaker Switch

The **LP-RU07101PDU** Power Distribution Unit includes a robust thermomagnetic breaker switch with finger guard, with a 1500 A current interruption capacity.



Figure 2



### Specifications

<b>Electrical Characteristics</b>	Values
Maximum power	1875 W
Voltage service rating	Up to 250 VAC (320 VAC max.)
Operating temperature range	-20 to +60 degrees Celsius
Thermomagnetic current breaker	15 A @ 125 VAC
Current breaker behavior	May trip between 101% and 134%, but must do it at 135% of rating within one hour at 25°C
Current interruption capacity	1500 A
Operation indicator	One red light
Cable size and length	10 ft (3 m) AWG#16 phase, neutral, ground with NEMA 5-15P
Mechanical Characteristics	Values
Number of outlets	Six (6)
Construction	Heavy duty steel enclosure
Mounting	Horizontal rack mounting
Length	19 inches
Height	1 U (U=rack units)

## How to Order

LP-RU07101PDU

Steel Body Power Distribution Unit, six (6) NEMA 5-15R outlets, 125 VAC, 50/60 Hz, maximum working current 15 A, 1875 W of maximum output power, protected with a 15 A thermomagnetic breaker switch with finger guard, 1500 A of interrupting capacity, indicator light. Width: 19", height: 1 U, and a 3 m 3x AWG#16 grounded power cord terminated with a NEMA 5-15P plug.

LanPro is continuously improving its products and reserves the right to change specifications and availability without prior notice.

www.lanpro.com