LP-RU07KM0022

KVM Modular style 8 Port PS2/USB Capable Switch, Digital video DVI connector, 19" Rack mountable. Height: 1U

LPRU07KM0022_SS_ENB01W

Features

- Control 8 computers with local or remote console.
- The console is compatible with PS2/USB mouse and keyboard. The computer is compatible with USB mouse and keyboard.
- Computer selection via front panel switches and OSD.
- LEDs display for easy status monitoring.
- Auto Scan Mode for monitoring all computers.
- Superior video quality.
- Easy installation no software required.
- Hot pluggable add or remove computers for maintenance without powering down the switch.
- Support cross-platform operation - Windows, Linux, Mac * and Sun *.





LP-RU07KM0022 KVM Modular style 8 Port PS2/USB Capable Switch, Digital video DVI connector, 19" Rack mountable. Height: 1U

LanPro KVM DVI Switch is a control unit that allow to access and control of up to 8 computers from a single PS2/USB keyboard, PS2/USB mouse, and monitor console.



A Specifications:

| Туре | | | 8 ports |
|------------------------|---------------------------|--------------------------|---|
| Model | | | LP-RU07KM0022 |
| Computer Connection | Direct Connects | | 8 |
| CPU Port Selection | | | OSD Menu, Front panel buttons, Hot Key |
| Connectors | Console Connector | Monitor | 1xDVI Type A Female |
| | | Keyboard | 1 x USB Type A Female |
| | | Mouse | 1 x USB Type A Female |
| | | Expansion Interface | 1 x USB Type A Female (Front expansion Keyboard, Mouse Interface) |
| | | Microphone | 8 x Mini Stereo Female (Pink) |
| | | Audio Speaker | 8 x Mini Stereo Female (Green) |
| | PC Connector | Mouse/Keyboard | 8 x USB Type B Female |
| | | Monitor | 8 x DVI-D |
| | | Mixed Audio Connector | 8 x Mini Stereo Female (Black) |
| | Power | | 1 x DC Jack |
| Toggle Switch | Connection Port Selection | | KVM Operation Panel Digital keys |
| | KVM Reset | | 1 x semi-embedded keys |
| LED's | Selected | | 8 x Green |
| | Online | | 8 x Red |
| Analog Mode | Keyboard/Mouse | | USB, PS2 |
| Resolution (Max) | | | 1920 x 1200 @ 60HZ Local & Remote |
| Scan time interval | | | 3, 5, 10, 15, 20, 30, 40, 60s (3s by default) |
| Operating Environment | | Operating temperature | -10-50°C |
| | | Storage temperature | -20-60°C |
| | | Humidity | 0-80%RH, No Condensation |
| Physical Properties | | Housing | Metal |
| | | Size | 432 x 155 x 44 mm |
| | | Weight | 1.82kg |

B How to Order:

LP-RU07KM0022 KVM Modular style 8 Port PS2/USB Capable Switch, Digital video DVI connector, 19" Rack mountable. Height: 1U.