

LP-RU07KMMX192 KVM Module style VGA 8 ports PS2/USB Capable Switch, with 19" LCD Display, Slim Keyboard, 19" Rack mountable with internal power supply 110/240V AC or DC and touch panel. Height: 1U.

LPRU07KMMX192_SS_ENB01W

Features:

- Front LCD Console (keyboard, mouse, monitor or 19") + KVM Module design (8 ports).
- It's very flexible and convenient for combination.
- IP optional (IP card could be installed inside KVM module).
- Extra prepositive USB mouse interface.
- Single port length: 462.6mm; Multi-ports length: 611mm. múltiples puertos: 611mm.



**LP-RU07KMMX192
KVM Module style VGA 8 ports PS2/USB
Capable Switch, with 19" LCD Display,
Slim Keyboard, 19" Rack mountable with internal
power supply 110/240V AC or DC
and touch panel. Height: 1U.**

The LanPro 19 "1U Rack Mount KVM Series monitors and controls up to 16 computers (expandable to 128 computers) helps to efficiently manage space. Display provides control over frequency, resolution, brightness, brightness from the video screen.

A Specifications

LCD CONSOLE SPECIFICATION

19" LCD Monitor	Aspect Ratio	19" screen, 16: 9	
	Video	Wide AHVA TFT-LCD	
	Visible square	409.8 (H) x 230.4 (V)	
	Color Support	16.7M, True 8 bit	
	Contrast	1000 : 1 (Typ)	
	Background Lighting	LED	
	Pixel size	300 x 300 um	
	LEDMTBF	100,000 hours	
	Input Power	12V	
Keyboard (detachable design)	Keyboard	100 keys, detachable (9 different languages to choose from)	
	IBM/AT Compatible	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10	
	Port	Standard PS/2; USB	
	Useful Life	>1,000,000 times	
Mouse	Type	Touch Screen	
	Port	PS/2 Standard	
	X/Y Resolution	>1000 dots/inch (40 x 40/mm)	
	Useful Life	>1,000,000 times	
Installation Dimension	407 x 445 x 45 mm		
Weight	6.15 kg		
SPECIFICATION OF KVM MODULAR			
Type	8 Ports		
Computer Connection	Direct Connections	8	
	Maximum Connections	128	
CPU port Selection	OSD Menu, front panel buttons, Hot key, IP remote control (Optional)		
Connectors	Console Connector	DB 37PIN	
	PC connector	Monitor, Keyboard / Mouse Module Switch	16 x VGA DB15, Blue female
	Power	1 x 110/240V AC or DC	
	Network Port	1 x RJ45	

SPECIFICATION OF KVM MODULAR			
Switch	Selection of connection port		KVM Operation Panel with Digital Keys
	KVM Reset		KVM Operation Panel with Digital Keys
	Reset IP Module		1 x semi-embedded Key
	Default IP module		1 x semi-embedded Key
LEDs	Selected		Nixie tube screen
	On-Line		16 x Red
	Red IP		1 x Green, 1 x Orange
Analog Mode	Keyboard / Mouse		USB, PS/2
Resolution (max)	1920 x 1200 @ 60Hz Local & Remote		
Scan Time Interval	3, 5, 10, 15, 20, 30, 40, 60s (3s by default)		
Operating Environment	Operating Temperature		-10-50°C
	Storage Temperature		-20-60°C
	Humidity	0-80%RH, Without condensation	
Physical Properties	Cover		Metal
	Dimension		148.4 x 445 x 45mm
	Weight		3.32 kg

B How to Order

LP-RU07KMMX192	KVM Module style VGA 8 ports PS2/USB Capable Switch, with 19" LCD Display, Slim Keyboard, 19" Rack mountable with internal power supply 110/240V AC or DC and touch panel. Height: 1U.
-----------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------