

LP-RU07KMXX
KVM Console Module Style PS2/USB Capable Switch, with 17" or 19" LCD Display, Slim Keyboard and Touchpad, 19" Rack mountable Unit. Height: 1U

LPRU07KVXX2_PFD_ENB01W

Features:

- Front LCD Console (keyboard, mouse, monitor 17" or 19") + KVM Module design (8/16ports).
- It's very flexible and convenient for combination.
- IP optional (IP card could be installed inside KVM module).
- Extra prepositive USB mouse interface.
- Single port length: 462.6mm; Multi-ports length: 611mm.



LP-RU07KMXX
KVM Console Module Style PS2/USB Capable Switch, with 17" or 19" LCD Display, Slim Keyboard and Touchpad, 19" Rack mountable Unit. Height: 1U

LanPro KVM Rack Series cost efficient 1U rack mountable Combo-free KVM unit monitors and controls up to 16 computers (expandable to 256 computers), assists in efficient management of valuable space. The series provides options of 17" or 19" LCD monitor. On Screen Display provides you with control over frequency, resolution, backlight luminance and brightness of the video display.

A Specifications:

LCD CONSOLE SPECIFICATION

17" LCD Monitor	Ratio	17" Screen, 4:3
	Video	SXGATFT-LCD
	Visible Square	337.920(H) × 270.336(V)
	Resolution (Max)	1280 x 1024 @60 Hz
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	Contrast	1000 : 1 (Typ)
	Backlight	LED
	Pixel Pitch	0.264 x 0.297 mm
	LEDMTBF	100,000 hours
	Input power	12V
19" LCD Monitor	Ratio	19" Screen, 16:9
	Video	Wide AHVA TFT-LCD
	Visible Square	409.8 (H) x 230.4 (V)
	Resolution (Max)	1366 x 768 @ 60Hz
	Support Color	16.7M, True 8 bit
	Contrast	1000 : 1 (Typ)
	Backlight	LED
	Pixel Pitch	300 x 300um
	LEDMTBF	100,000 hours
	Input power	12V
Keyboard (demountable design)	Keyboard	100 Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolución	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times
Installation Dimension	407 x 445 x 45 mm	
Weight	6.15 kg	

KVM MODULE SPECIFICATION		
Type	8/16 Ports	
Computer Connection	Direct Connects	8/16
	Maximum Connects	128/256
CPU Port Selection	OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)	
Connectors	Console Connector	DB 37PIN
	PC Connector	Monitor, Keyboard/Mouse Switch Module
	Power	1 x DC Jack
	Network Port	1 x RJ45
Switch	Connection Port Selection	KVM Operation Panel Digital keys
	KVM Reset	KVM Operation Panel Function Keys
	IP Module Reset	1 x semi-embedded key
	IP Module Default	1 x semi-embedded key
LED'S	Selected	Nixie Tube Display
	Online	16 x Red
	IP Network	1 x Green, 1 x Orange
Analog Mode	Teclado/Mouse	USB, PS/2
Resolution (Max)	1920 x 1200 @ 60HZ Local & Remote	
Scan time interval	3, 5, 10, 15, 20, 30, 40, 60s (3s by default)	
Operating Environment	Operating temperature	-10-50°C
	Storage temperature	-20-60°C
	Humidity	0-80%RH, No Condensation
Physical Properties	Housing	Metal
	Dimension	148.4 x 445 x 45mm
	Weight	3.32 kg

B How to Order:

LP-RU07KMXXPTP

LP-RU07KM	XX	P
KVM Module Style	LCD Monitor 17 - 17" 19 - 19"	Ports Blank - 8 ports 1 - 16 ports
T		P
Type 1- 110/220 External Power Supply 2- 110/220 Internal Power Supply 3- 12V Power Supply 4- 24VDC Power Supply 5- 48 VDC Power Supply 6- 125 VDC Power Supply		Product Blank - VGA Default 1 - VGA and IP Remote Control

Examples:

LP-RU07KM171	KVM Module style VGA 8 ports PS2/USB Capable Switch, with 17" LCD Display, 19" Rack mountable. Height: 1U.
LP-RU07KM1711	KVM Module style VGA 16 ports PS2/USB Capable Switch, with 17" LCD Display, 19" Rack mountable. Height: 1U.
LP-RU07KM191	KVM Module style VGA 8 ports PS2/USB Capable Switch, with 19" LCD Display, 19" Rack mountable. Height: 1U.
LP-RU07KM1911	LP-RU07KM1911 - KVM Module style VGA 16 ports PS2/USB Capable Switch, with 19" LCD Display, 19" Rack mountable. Height: 1U.