LP-VR71210642 VersaLine 7000 Series 42 U Four Post OpenRack with 520 mm width and 22 in (558.8 mm) to 40 in (1016 mm) adjustable depth.

LPVR71210642 _SS_ENB01W

Features

- Supports up to 1000lb (453.6 Kg) of rack-mount equipment.
- Adjustable depth for versatility from 22 in (558.8 mm) to 40 in (1016mm).

Flat-packed design reduces handling costs.

- Easy assembly at the point of installation for rapid deployment.
- Full steel construction for superior durability and stability.
- Mount standard networking equipment using standard cage nuts and screws that conform to EIA - 310D.
- Durable Black color powder epoxy coating.
- Bolts directly to floor through prepared access points or with (optional) Casters.
- Self-Squaring design.
- U markings printed on 19" rails for easy location.
- Button holes for easy installation of Cable management ducts and/or Power Distribution Units (PDU's).
- Cable management hoops included.







LP-VR71210642

VersaLine 7000 Series 42 U Four Post OpenRack with 520 mm width and 22 in (558.8 mm) to 40 in (1016 mm) adjustable depth.

The **VersaLine LP-VR71210642** 42 U four (4) Post Open Frame Rack fully made of cold rolled steel provides greater versatility, durability and stability, reducing the need for concrete mounting kits.

A cost-effective solution for mounting network equipment and telecom equipment, this four post rack features **Tool-Less** holes for button mounted cable managers or Power Distribution Units (PDU's) and square mounting holes on the frame that allow you to easily mount ANSI/EIA RS-310-D compliant network equipment without additional hardware. Package also includes Cable management hoops (Rings) and Casters.



Easy to deploy, the VersaLine LP-VR71210642 four post open frame rack can be easily assembled in minutes and is backed by LanPro's Lifetime Warranty - ensuring a permanent Server/Telecom storage solution.

Our multiuse four post rack VersaLine LP-VR71210642 is a cost and space effective way to install a variety of 19" equipment. Intended primarily for patch panels or network switching equipment, the four post rack can also be fitted with shelves to support equipment.

Depth is adjustable in one inch increments.

Applications

Server rooms or other locations where telecomm and networking equipment need to be housed.

Specifications

| Rack Type | 4-Posts |
|------------------------------|--|
| U-Height | 42U |
| Frame Type | Open Rack |
| Industry Standards | DIN41494 |
| | EIA RS310-D |
| | IEC297-3-100 |
| | ROHS |
| Performance | |
| Weight Capacity (Stationary) | 1000 lb (453.6kg) |
| Physical Characteristics | |
| Color | Black |
| Internal Width | 18.3 in (465 mm) |
| External Width | 20.08in (510 mm) |
| External Height | 79.1 in (2009.1 mm) |
| External Depth | Min: 22 in (558.8mm) Max:40 in (1016mm) |
| Product Weight | 54 lb (24.3 kg) |
| Post width | 1.18 in (30 mm) |
| Post Depth | 2.95 in (75 mm) |
| Packaging Information | |
| Flat Pack | Yes |
| Shipping (Package) Weight | 55 lb (24.75 kg) |
| Shipping Dimensions (HWD/in) | 81 x 8 x 5 |
| Shipping Dimensions (HWD/mm) | 2057 x 203.2 x 127 |



Shipping Package





Depth adjustment

The Rack depth is adjustable in one (1) inch increments as per the following table:

| Rack Adjustable Depth Index Numbers | |
|-------------------------------------|---------------|
| Mounting Depth | Index Numbers |
| 22 in / 558.8 mm | 0 and 0 |
| 23 in / 584.2 mm | 1 and 0 |
| 24 in / 609.6 mm | 1 and 1 |
| 25 in / 635.0 mm | 1 and 2 |
| 26 in / 660.4 mm | 2 and 2 |
| 27 in / 685.8 mm | 2 and 3 |
| 28 in / 711.20 mm | 3 and 3 |
| 29 in / 736.6 mm | 3 and 4 |
| 30 in / 762.00 mm | 4 and 4 |
| 31 in / 787.4 mm | 4 and 5 |
| 32 in / 812.8 mm | 5 and 5 |
| 33 in / 838.2 mm | 5 and 6 |
| 34 in / 863.6 mm | 6 and 6 |
| 35 in / 889.0 mm | 6 and 7 |
| 36 in / 914.4 mm | 7 and 7 |
| 37 in / 939.8 mm | 7 and 8 |
| 38 in / 965.2 mm | 8 and 8 |
| 39 in / 990.6 mm | 8 and 9 |
| 40 in / 1016.0 mm | 9 and 9 |

Note: Depth from 22 to 40 inches (1-inch increments) is available by adjusting the beams at corresponding silkscreen numbers on them.

How to Order

LP-VR71210642 VersaLine 7000 Series 42 U Four Post OpenRack with 520 mm width and 22 in (558.8 mm) to 40 in (1016 mm) adjustable depth.

LanPro is continuously improving its products and reserves the right to change specifications and availability without prior notice.