

LP-OC33130027ZF Drop Fiber Optical Cable with two (2) Colored coating fiber, LSZH-rated Jacket, self supporting, central steel wire, Bow type, Two Strength members FRP and 2 singlemode ITU-T G657.A2 fiber cores.

LPOC33130027ZF_SS_ENB01W

Features:

- Special low-bend-sensitivity fiber provides high bandwidth and excellent communication transmission properties.
- Simple structure, light weight, high tensile strength.
- 2 Fiber singlemode ITU-T G657.A2.
- Two parallel FRP strength members ensure good performance of crush resistance to protect the fiber.
- A steel wire is added for self support enabling it to be used in outdoor aerial Fiber To The Home (FTTH) applications.
- Novel groove design, easily strip and splice, simplified installation and maintenance.




**LP-OC33130027ZF
Drop Fiber Optical Cable FTTH
(Fiber-to-the-home) with two (2) Colored coating fibers,
LSZH-rated Jacket, self supporting, central steel wire,
Bow type, Two Strength members FRP and 2 singlemode
ITU-T G657.A2 fiber cores.**

The **LP-OC33130027ZF** is a family of cables designed for Fiber-To-The-Home (FTTH) Aerial Outdoor environment applications.

The optical fibers are placed in the center. Two FRP strength members are placed at the sides. A steel wire is added for self support enabling it to be used in outdoor aerial Fiber-To-The-Home (FTTH) applications.

LanPro uses only the finest fiber strands brands in the world. Usually from Corning® but also from Prysmian® or other recognized brands depending on the availability at the moment of the production.

A Cable Section



B Cable Parameters

ITEMS		SPECIFICATIONS
Fiber Count		2
Colored Coating Fiber	Dimension	250 ± 15 µm
Strength Member	Dimension	0.5 mm
	Material	FRP
Self Supporting Member	Dimension	1.0 mm
	Material	Steel
Jacket	Dimension	5.3 ± 0.2 mm x 2.2 ± 0.1 mm
	Material	LSZH
	Color	Black

C Mechanical and Environmental Characteristics

ITEMS	UNITS	SPECIFICATIONS
Tension (Long Term)	N	300
Tension (Short term)	N	600
Crush (Long Term)	N/10 cm	300
Crush (Short Term)	N/10 cm	2200
Min. Bending Radius (Dynamic)	mm	20 D
Min. Bending Radius (Static)	mm	10 D
Installation Temperature	°C	-10 to +50
Operating Temperature	°C	-20 to +65
Storage Temperature	°C	-20 to +65
Attenuation (1310/1550 nm)	dB/km	≤0.4 / ≤0.3
Nominal linear weight	kg/km	≤25

D How to Order**LP-OC33130027ZF**

Drop Fiber Optical Cable FTTH (Fiber-to-the-home) with two (2) Colored coating fibers, LSZH-rated Jacket, self supporting, central steel wire, Bow type, Two Strength members FRP and 2 singlemode ITU-T G657.A2 fiber cores.