

LanPro®, Corning® Optical Fiber.

LPOCCORNING_AN_ENB01W



LanPro®, Corning® Optical Fiber.

Names that are synonymous with cable and fiber combine to create the ultimate in fiber optics. LanPro partners with Corning Optical Fiber to deliver the world's most reliable and technologically advanced optical fiber cables.

A Singlemode

Standard

LanPro utilizes Corning® SMF-28e+™ fiber as its standard singlemode offering. This is a full-spectrum fiber that is fully backward-compatible with legacy singlemode fiber. It enables increased optical launch power of legacy singlemode fiber, improved macrobend specifications from 0.05 dB to 0.03 dB, and tighter zero dispersion wavelength (λ_0) tolerance from a range of ± 10 nm to ± 7 nm. This fiber supports all broadband applications and complies with the most stringent industry standards, such as:

- ITU-T G.652 (Tables A, B, C and D).
- IEC 60793-2-50 Type B1.3.
- TIA/EIA 492-CAAB.
- Telecordia GR-20-CORE.

Long-Haul

For long-haul applications, rely on LanPro and the technology of Corning® LEAF® fiber. This is the most widely deployed non-zero dispersion shifted (NZ-DSF) fiber in the world and the first low water peak NZ-DSF fiber. Its large effective area and industry-leading polarization mode dispersion (PMD) specifications enable 10 Gb/s and 40 Gb/s network systems of the future.

ClearCurve® ZBL

Lanpro, utilizing Corning® ClearCurve® ZBL Optical Fiber, delivers the best macrobending performance in the industry while maintaining compatibility with current optical fibers, equipment, practices and procedures. This fullspectrum singlemode optical fiber, when subjected to smaller radii bends, experiences virtually no signal loss. ClearCurve fiber exceeds the most stringent bend performance requirements of ITU-T Recommendations G.657. B3 while remaining fully compliant with ITU-T Recommendation G.652.D and the installed base of Corning SMF-28e® and SMF-28e+® fiber.



B Multimode**ClearCurve® Multimode Fiber**

Corning® ClearCurve® ultra-bendable laser-optimized™ multimode optical fiber delivers the best macrobending performance in the industry while maintaining compatibility with current optical fibers, equipment, practices and procedures. ClearCurve OM3/OM4 multimode fiber is designed to withstand tight bends and challenging cable routes with substantially less signal loss than conventional multimode fiber.

These fibers have superior measurement technology and manufacturing control, and industry-leading CPC® coatings for superior microbend and environmental performance.

ClearCurve fiber performance is ensured by minEMBC, the industry's leading standards-approved bandwidth measurement for OM3 fibers. ClearCurve fibers are the only ones to use this measurement to ensure 10 Gb/s performance.

62.5 micron

These fibers support data rates of 1 Gb/s in both the 850 nm and 1300 nm windows. They comply with the most stringent industry standards, such as:

- ISO/IEC 11801, type OM1 fiber.
- IEC 60793-2-10, type A1b fiber.
- TIA/EIA, 492AAAA-A.

50 micron

These fibers support data rates of 10 Gb/s at 850 nm. They also comply with the most stringent industry standards, such as:

- ISO/IEC 11801, type OM2, OM3 and OM4* fibers.
- IEC 60793-2-10, type A1a.1, A1a.2 and A1a.3* fibers.
- TIA/EIA, 492AAAB, 492AAAC-A and 492AAAD.

* Assumes IEC draft standard is harmonized with 492AAAD, which was approved by TIA.

C Cross Reference table

Fiber Type	LanPro	Corning® OpticalFiber	Description
Standard Loose Tube SM	ZC	SMF-28e+ Fiber	Full spectrum, low water peak singlemode, ITU-T G.652D
Performance Loose Tube SM	ZB	SMF-28e+ Fiber	Full spectrum, high performance low water peak singlemode with 0,35/0,25 attenuation, ITU-T G.652D
Tight Buffer SM	ZE	SMF-28e+ Fiber	Full spectrum, low water peak singlemode with 900µm PVC buffer, ITU-T G.652.D
Long-Haul SM	ZG	LEAF® Fiber	Large Aeff, low water peak, NZ-DSF singlemode, ITU-T G.655
Ultra-Bendable SM	ZA	ClearCurve® ZBL	Full spectrum with best macrobending performance, ITU-T G.652.D and ITU-T G.657.A
62,5 µm MM	QG	Infi niCor® 300 Fiber	1 Gb/s < 300 m at 850 nm, OM1* 1 Gb/s < 550 m at 1300nm
62,5 µm MM	QL	Infi niCor® CL 1000 Fiber	1 Gb/s < 500 m at 850 nm, OM1* 1 Gb/s < 1000 m at 1300nm
Ultra-bendable 50 µm MM	TM	ClearCurve® OM2 Fiber	10 Gb/s < 150 m at 850 nm, OM2* 1 Gb/s < 750 m at 850nm
Ultra-bendable 50 µm MM	TP	ClearCurve® OM3 Fiber	10 Gb/s < 300 m at 850 nm, OM3* 1 Gb/s < 1000 m at 850nm
Ultra-bendable 50 µm MM	TG	ClearCurve® OM4 Fiber	10 Gb/s < 550 m at 850 nm, OM4* 1 Gb/s < 110 m at 850 nm
Ultra-bendable 50 µm MM	TI	ClearCurve® OM4 Fiber	10 Gb/s < 600 m at 850 nm, OM4+* 1 Gb/s < 1100 m at 850nm

* Designation per ISO 11801 Fiber Standards.