



Model	MicroFlow Touch	MiniFlow Rapid	PowerFlow	MultiFlow
<b>Typical Usage</b>	Inside Plant	In/Outside Plant	Outside Plant	Outside Plant
<b>Fiber/Cable Diameter</b>	0,8-5,5 mm	4-12 mm	8-25 mm	8-32 mm
<b>Tube Size (OD)</b>	5-16 mm	7-20 mm	18-70 mm	18-70 mm
<b>Part #</b>	101-10005	101-10031	101-10001	101-10002
<b>Install Speed to</b>	90 m/min.	100 m/min.	80 m/min.	80 m/min.
<b>Distance</b>	Up to 2.5 km	Up to 3.5 km	Up to 10 km*	Up to 10 km*
<b>Recommended Airflow Recommended Pressure</b>	200-500 l/pr. min. 8-16 bar air	1.000 l/pr. min. 8-16 bar air	8.000-12.000 l/pr. min. 8-12 bar air	8.000-12.000 l/pr. min. 8-12 bar air
<b>Length: Width: Height: Weight:</b>	<b>Machine:</b> 25 cm <b>Control Box:</b> 25 cm 15 cm 16 cm 22 cm 13 cm 9,7 kg. 1,9 kg.	650 mm 225 mm 210 mm 24 kg.	650 mm 230 mm 350 mm 38 kg.	700 mm 230 mm 350 mm 40 kg.
<b>Unique Features</b>	Automatic Buckle Detection Adjustable Torque Preset Automatic Stop Adjustable Speed Control Speed, Torque & Count Display Air Pressure & Flow Regulation Easy to Operate Simple Maintenance	Use with Air or Water Push Force Monitor Rugged Construction Flexible Adaptability Adjustable Torque Distance and Speed measurement Ease of Use Simple Maintenance	Use with Air or Water* Installs Single Cable Rugged Construction Flexible Adaptability Adjustable Torque Distance and Speed measurement Ease of Use Simple Maintenance	Use with Air or Water* Jets Tubes or Cable Rugged Construction Flexible Adaptability Adjustable Torque Distance and Speed measurement Ease of Use Simple Maintenance



For further information please contact:

