

**LP-CC041205GRC**

**Unshielded Control Cable Security and audio, CMR-rated, AWG 22, 4 stranded copper conductors, Gray color jacket in 1000ft (305m) spool**

LPCC041205GRC\_SS\_ENB01W

**Applications**

- Alarm, Control, Sound.
- PA, Signaling.
- Electrical and RF.
- Noisy Locations.

**LP-CC041205GRC**

**Unshielded Control Cable Security and audio,  
CMR-rated, AWG 22, 4 stranded copper conductors,  
Gray color jacket in 1000ft (305m) spool**

Security, Sound and Control Cable, (available Riser-CMR, CM and LSZH), 22 AWG stranded copper conductors, polypropylene insulation, Unshielded.



**A Specifications**

<b>Conductors</b>	<b>No. Conductors</b>	4
	<b>AWG</b>	22
	<b>Stranding</b>	7x30
	<b>Conductors Material</b>	BC - Bare Copper
	<b>Jacket Material</b>	PP - Polypropylene
	<b>Nom. Thickness</b>	0.009in (0.22 mm)
	<b>Nom. Insulation Diameter</b>	0.009in (0.22 mm)
	<b>Color Code</b>	Black, Red, White, Green
<b>Outer jacket</b>	<b>Material</b>	CMR
	<b>Nom. Thickness</b>	0.018 in (0.44 mm)
	<b>Nom. Diameter</b>	Black, Red, White, Green
	<b>Ripcord</b>	Yes
	<b>Overall, Cable Diameter (Nominal)</b>	0.142in (3.6 mm)
<b>Electrical</b>	<b>Nom. Conductor DCR</b>	16.8 Ohm/1000ft (305m)
	<b>Nom. Capacitance Cond-to-Cond</b>	18 pF/ft
	<b>Max. Current</b>	4.9 Amps per wires @25°C
<b>Mechanical Characteristics</b>	<b>Operating Temperature</b>	-20°C a +75°C
	<b>Max. Pull Tension</b>	38 lbs (17kg)
	<b>Bulk Cable Weight</b>	14 lbs/1000ft
<b>Standards and Compliance</b>	<b>Environmental Suitability</b>	Indoor Options - CMR Riser, CM and LSZH
	<b>Flammability / Reaction to Fire</b>	UL 1666 Riser, IEEE 1202 FT4, IEC 60332-1-2

**B Variations**

<b>Model</b>	<b>Description</b>
<b>LP-CC041105GRC</b>	Unshielded Control Cable Security and audio, CM-rated, AWG 22, 4 stranded copper conductors, Gray color jacket in 1000ft (305m) spool.
<b>LP-CC041J05GRC</b>	Unshielded Control Cable Security and audio, LSZH-rated, AWG 22, 4 stranded copper conductors, Gray color jacket in 1000ft (305m) spool.

**C How to order**

<b>LP-CC041205GRC</b>	<b>Unshielded Control Cable Security and audio, CMR-rated, AWG 22, 4 stranded copper conductors, Gray color jacket in 1000ft (305m) spool.</b>
-----------------------	--

*LanPro is continuously improving its products and reserves the right to change specifications and availability without prior notice*