

LP-F51AXX LanPro Aluminum Single Tangent support for ADSS cable

LPF51AXX_PFD_ENB01W

Features:

- May be used as a pull-through by removing the bushing inserts.
- Double cable supports option.
- High-strength aluminum.
- Smaller and more compact design.
- Facilitates faster installation.
- Versatile mounting styles to fit different structure types: bolted, banded or standoff.
- Lowers the total cost of installation.



LP-F51AXX LanPro Aluminum Single Tangent support for ADSS cable

LanPro's Aluminum Single tangent supports for ADSS Cables with various mounting capabilities: bolted, banded or standoff. LanPro's Aluminum Single tangent supports for ADSS Cables reduce installation costs by functioning as a pull-through during installation.



B How to Order:

LP-F51TMO

LP-F	51	Fiber Optical Hanging and Support Systems
Support Type		
T	A	Aluminum Single Tangent support for ADSS
	B	Aluminum Double Tangent support for ADSS
	C	Drop Tangent support for ADSS
	D	Free
Mounting type		
MM	A	Bolted
	B	Banded
	C	Standoff
	D	Free
ADSS Outside Diameter		
O	A	5.7mm to 6.9mm (OD cable)
	B	7mm to 8.2mm (OD cable)
	C	8.3mm to 9.4mm (OD cable)
	D	9.5mm to 10.7mm (OD cable)
	E	10.8mm to 12mm (OD cable)
	F	12.1mm to 13.3mm (OD cable)
	G	13.4mm to 14.6mm (OD cable)
	H	14.7mm to 15.9mm (OD cable)
	J	16mm to 17.1mm (OD cable)
	K	17.2mm to 19.1mm (OD cable)
	M	19.2mm to 21mm (OD cable)
	N	21.1mm to 22.9mm (OD cable)
	O	23mm to 24.8mm (OD cable)
	P	24.9mm to 26.7mm (OD cable)
	Q	26.8mm to 28.6mm (OD cable)
	R	28.7mm to 30.5mm (OD cable)
	S	30.6mm to 32.4mm (OD cable)
T	32.5mm to 34.3mm (OD cable)	
U	34mm to 36.3mm (OD cable)	

Example:

LP-F51AAE LanPro Aluminum Single Tangent support for ADSS cable, Bolted, up to 600' (183 m) span and 5.7mm to 6.9mm.