

LP-FLSCS16212 - FusionLess® 2 Connector, SC, Singlemode, APC Polish, compatible G.652.D and G.657.A 9/125µm, Drop type Fiber cable 2x3mm and 1.6x2mm, Green Housing

LPFLSCS16212_SS_ENB01W

Features

- Quick and easy fiber termination.
- Available to re-use.
- High success rate of connection.
- Superior optical characteristic value.
- Simple assembly process.
- No failure after opening.

Applications

- Fiber Optic Telecommunication.
- Fiber Distribution Frame.
- FTTH Outlets.
- Optical Cable Interconnection.
- Cable Television.



**LP-FLSCS16212
FusionLess® 2 Connector, SC, Singlemode,
APC Polish, compatible G.652.D and G.657.A
9/125µm, Drop type Fiber cable 2x3mm and
1.6x2mm, Green Housing**

The FusionLess® 2 Optical Mechanical Connectors by LanPro is the most widely used fiber optic connector in FTTx that does not need epoxy or polishing.

It enables fast and on-site installation of 1.6 x 2.0mm and 2.0 x 3.0mm cable type connectors even when the user has no access to power. Two or three pieces of the preassembled and factory terminated connectors can be installed within 2 minutes using simple tools and can be recycled several times.

It accommodates a reliable and durable optical network especially suitable for advanced fiber optic systems requiring exceptional stability and low loss.

This connector pass all test under Telcordia GR326

A Connector Construction:

Fiber type:

- **SM:** Standard Singlemode fiber type

Ferrule Polishing type:

- **APC type:** Angled Physical Contact type

Connector type for using cable type:

- 2.0mm X 3.0mm (Flat) type
- 1.6mm X 2.0mm (Flat) type

B Product Specifications:

Item	Specification
Standard	TIA/EIA 604-3, IEC 61754-4, RoHS
Insertion Loss	Typ. 0.3dB / Max. 0.5dB
Return Loss	>55dB(APC)
Endurance	Up to 5 times reconnection / ≤0.2dB
Tension	(2.0mm x 3.0mm) 4.0kg / ≤0.2 dB change (1.6mm x 2.0mm) 2.0kg / ≤0.2 dB change
Holding force	40N
Temperature Change	21 time / -40°C ~ 85°C / ≤ 0.2 change
Operation temperature	-20 °C a 60 °C

End Face Geometry	APC Type
Radius of Curvature (nm)	5~12
Apex Offset (um)	Less than 50
Fiber Height (nm)	±50
Tilt Error on APC 8'	±0.2

C How to Order:**LP-FLSCS16212**

FusionLess® 2 Connector, SC, Singlemode, APC Polish, compatible G.652.D and G.657.A 9/125µm, Drop type Fiber cable 2x3mm and 1.6x2mm, Green Housing